

No.	Name	Specification Parameters	Pictures
1	Coiled Tubing Main Equipment	Integrated trailer type; Inject head lifting force of 100000 pounds and setting force of 50000 pounds; Drum capacity 1 3/4 "-8000m, 2" -6400m; Spray box 4 1/16 "-15K psi; Blowout preventer 5 1/8 "-15K psi	
2	Continuous Oil Tubing	Length 7000m; Outer diameter size 1 3/4 "; Equal wall thickness (0.204in) Pressure bearing 10K psi	
3	Coiled Tubing	Length 7000m; Outer diameter size 1 3/4 "; Variable wall thickness (0.204-0.188-0.175-0.156in) Pressure bearing 10K psi	
4	Mixed Liquid Trailer Pump	Exit 4 "206 is controlled by a gate, with two exits located at the tail of the pump bar; Import 4 "206 union, with 3 inlet ports on each side of the lever, and a gate for separate control; Two independent mixing tanks, each with 75bbl; Can independently supply water and liquid; Centralized control of the control panel; Flow meters are suitable for diesel, chemical agents, naphtha, etc	

5	Piston Pump Trailer Pry	<p>Export 2 "1502 Union B Import 4 "206 Union P Dual machine dual pump, 600HP * 2; Single pump displacement 40-600L/min (0.26-3.77BPM); The maximum working pressure is greater than 10K psi; Corrosion and oil resistance; Equipped with a remote control box, capable of remote operation and data collection</p>	
6	Nitrogen Generator Trailer Pry	<p>Specification and model: MZD-1200/500-95% - C Maximum displacement of 1200m3/h (flow: 706 scfm); Maximum pressure 50MPa (presion: 7250psi); Purity adjustable from 95-99% (pureza: 95% -99%) Export 2 "1502 Union B Export equipped with one-way valve 2 "1502 10000psi</p>	
7	Liquid Storage Tank	<p>Trailable, landing during operation; 80m3 (500BLS) Import and export 4 "206 union (b), set at the lowest point at both ends of the tank, controlled by gates Oil resistant and clear liquid volume display</p>	
8	Waste Liquid Tank	<p>Trailable, landing during operation; 80m3 (500BLS) 500bbl Imported 3 "206 union (b), U-shaped pipe enters from the upper end of the tank Exit 4 "206 union (b), set at the lowest point at both ends of the tank, controlled by gates Oil resistant and clear liquid volume display</p>	

9	Sand Jar	<p>Trailable, landing during operation; 80m3 (500BLS)</p> <p>Imported 2 "1502 from the top of the tank with a U-tube</p> <p>Exit 4 "206 is set at the lowest point at both ends of the tank, controlled by gates</p> <p>There is an inlet on the top of the tank, which allows people to clean the sand inside</p>	
10	Emergency Hydraulic Valve	<p>10K psi;</p> <p>Material with slight sulfur resistance</p> <p>Diameter 3 1/16 ";</p> <p>Can be manually pressurized and controlled, and can be operated in a coiled tubing control room;</p> <p>Diameter 3-1/16 inches;</p> <p>Pressure bearing 10000psi;</p> <p>Export 3 "1502 union (or with conversion flange)</p> <p>Imported 3-1/16 inch 10000psi flange (with bolts and steel rings)</p> <p>Equipped with a large displacement dual channel manual hydraulic pump and remote control flat valve switch (2 sets of 5m and 15m hydraulic pipelines)</p>	
11	Cyclone Desander	<p>10K psi;</p> <p>Material with slight sulfur resistance</p> <p>Imported 3 "1502 union</p> <p>The gas-liquid outlet is 3 "1502 from Renb</p> <p>Sand mouth is 2 "1502 union</p> <p>Appearance dimensions: height 3.7m, diameter 0.92m</p>	

12	Chip Catcher	<p>Diameter 3-1/16 inches Pressure bearing 10000psi Material with slight sulfur resistance Imported 3 "1502 union (or with conversion flange) Export is 3 "1502 union (or equipped with conversion flange) Middle straight channel, controlled by flat valve The front and rear of the debris trap are connected by a union, making it easy to disassemble The pressure and release can be observed before and after the debris trap</p>	
13	Choke Manifold	<p>Diameter 3-1/16 inches Pressure bearing 10000psi Material with slight sulfur resistance Adjustable and adjustable Imported 3 "1502 union (or with conversion flange) Export is 3 "1502 union (or equipped with conversion flange) Observable pressure for import and export Middle straight channel, controlled by flat valve Adjustable oil nozzles (throttle valves) on both sides Removable oil nozzle cover (with oil nozzle wrench and spare oil nozzles of various models), requiring quick replacement, and the oil nozzle cover can be pressed back and forth</p>	
14	Separator	<p>1450psi Import connection 3 "1502 is connected to the tank through a 6-point gradient pipe; Liquid outlet 3 "pipe external connection 3" 206 union Gas outlet 6 "pipe external connection 4" 206 union b</p>	

		Gas processing capacity of 40MMPCND (1330000m3/d); Liquid processing capacity of 20MBPD (3180Km3/d) Gas and liquid flow meters are required	
15	Separator	1450psi Import connection 3 "1502 is connected to the tank through a 6-point gradient pipe; Liquid outlet 3 "pipe external connection 3" 206 union Gas outlet 6 "pipe external connection 4" 206 union b Gas processing capacity of 30MMPCND (850000m3/d); Liquid processing capacity 5MBPD (800m3/d) Gas and liquid flow meters are required	
16	Torch	Import 4 "206 Union P Automatic ignition, no need for external power (solar energy storage) Equipped with anti backfire device Manual ignition backup Equipped with tension ropes and ground anchors Height 12m Diameter of 8 inches	
17	Alternator	5 units of 100KW and 1 unit of 200KW; Interface of each unit: Export 110V explosion-proof plug (1 piece) Export 220V explosion-proof plug (3 pieces) Export 380V explosion-proof plug (1 piece)	

18	Duty Room	<p>Trailer type Entrance ladder Two explosion-proof lighting fixtures at the top illuminate the well site Including a simple toilet There is a side ladder that allows access to the roof Explosion proof air conditioner, external unit grounding hand sink Eye wash basin Office desk fixed floor Long chair with fixed floor bottom for storage File cabinet fixed floor Insulated hot water kettle Imported explosion-proof plug Indoor leakage protection Outdoor diagonal grounding</p>	
19	Crane	<p>80t Remote control available, with spare remote control included Lightweight pad Used in South America, suitable for local diesel engines</p>	
20	Crane	<p>25t Remote control available, with spare remote control included Lightweight pad Equipped with a fixed and adjustable climbing operation basket Used in South America, suitable for local diesel engines</p>	
21	Truck Mounted Crane	<p>Box board length 8.2 meters Front 4 and rear 8 models 16t folding arm</p>	

22	Fuel Truck	6m3	
23	Vacuum Tanker Truck	<p>Capacity 160bbl</p> <p>Vacuum negative pressure suction of air compressor</p> <p>Vacuum positive pressure drainage of air compressor</p> <p>Import and export gate control, buckle type 4 "209, removable and replaceable</p> <p>Trailer type</p>	
24	Truck Tractor	500HP	
25	Trailing Tablet	17m	
28	Mechanical Testing Vehicle	<p>Purchase optical fiber 0.125 "-7600m;</p> <p>Purchase 3BLS sealing oil for cable spray preventer</p>	

29	Lift Up Lighting Fixture	<p>Can generate diesel power independently and can be connected to an external 220V power source; Capable of exporting 220V and 24V power supplies</p>	
30	Underground Tools		
31	Convert Flange Class		
32	Pipeline Category		